





ICEBERG Undersink Water Chiller

The Iceberg is our innovative new undersink water cooler, which supplies cooled, filtered water on demand from a counter-mounted tap adjacent to your sink or handbowl. The impressively quiet electric refrigeration unit installs discretely inside your base cupboard and can dispense a cool 11.5 litres an hour.

Created especially to accommodate small spaces conventional dispensers are too large for. Measuring only 12" x 16" x 12", the Iceberg's compact design will easily fit under most sinks. An impressive output capacity of 3 gallons per hour, the compressor driven chiller provides exceptional cooling performance. Simply connect the Iceberg to a countertop mounted faucet for cold water on demand.



Features

- #304 stainless steel cold water reservoir
- Copper evaporator
- Adjustable cold water thermostat
- Powder coated cold rolled steel casing
- Sink mounted faucet not included
- Pressure Reducing Valve and Shock Arrestor protect from water mains pressure surges

Performance and Specifications

General

Undersink pressure tank water cooler, with a stainless steel cold tank

Performance

Cold water outlet temperature 4-10°C (39.2-50°F) Units designed for and tested in extreme temperatures for robust performance in all climates

Power Consumption 0.2 kw.hr/24hr

Cooler Cabinet Powder-coated painted 18SWG cold rolled steel

Compressor

Hermetically sealed, PTC starter with overload protector Refrigerant charge: 35.0g (1.2oz) R134a (Ozone friendly) (220~240VAC 50Hz) (100~115VAC 60Hz) The maximun inlet water pressure:80 PSI (0.552Mpa) The minimun inlet water pressure:20 PSI (0.138Mpa)

Dimensions and Freight Data Product Dimensions 300mm deep x 410mm wide x 300mm high (12" deep x 16.5" wide x 12" high)

Product Weight: 12.5kg (27.6 lb)

Product Boxed Dimension 330mm deep x 430mm wide x 340mm high (13" deep x 16.9" wide x 13.5" high)

Product Boxed Weight: 13.6kg (30.1 lb)

20FT Container Quantity: 637 Units 40FT Container Quantity: 1323 Units





ICEBERG

Undersink Water Chiller



All performances are tested in a controlled environment, certified by a third party. To learn more about these standards, please speak to your Crystal Mountain representative.





Crystal Mountain Products Limited

European Sales Office Fence House, Fence Avenue Macclesfield, Cheshire United Kingdom SK10 1LT Tel: +44(0) 1625 439 111 Fax: +44 (0) 1625 502 527 E-mail: cmeurope@crystalcoolers.com

North American Sales Office

200 Carnegie Drive, Suite 234 St. Albert, AB, T8N 5A7 Canada Toll Free: 800 878 6422 Tel: 1 780 454 4545 E-mail: sales@crystalcoolers.com

Crystal Mountain Products Inc. US Office / Warehouse

1000 H Taylor Station Rd Gahanna OH 43230 Tel: (614) 454 1618 Fax:(614) 409 9782 E-mail: sales@crystalcoolers.com

Crystal Mountain International Limited

Hong Kong Sales Office

Room 610, Winfield Commercial Building 6-8a Prat Avenue, Tsimshatsui Kowloon, Hong Kong Tel: (852) 2368 1989 Fax: (852) 3017 6727 E-mail: cmasia@crystalcoolers.com

CE COULUS LISTED CB C SASO ISO9001 WEEE ROHS

Website: www.crystalcoolers.com

Crystal Mountain has a policy of continuous development and reserves the right to change specifications without notification.