RO SYSTEMS - Z1



UNDER SINK RO

The SPECTRUM Z1 combines sleek design with outstanding functionality, making it an ideal choice for both residential and light commercial water filtration. Its compact, easy-to-use setup features twist-and-click cartridge loading and push-fit connections, ensuring quick installation and hasslefree maintenance.

Equipped with cartridge change monitors and autoflush settings, the Z1 keeps your system performing at its best, ensuring consistent, high-quality water. It comes complete with all the necessary fittings, including an isolation valve, tubing, connections, and a stylish brushed stainless-steel tap.



TECHNICAL DATA

 \square

5-38
1
<500
65
93
220 VAC 50 Hz

ર્દુંુટે

<1

Maximum Feed Water Turbidity (NTU)

COMPONENTS

- Z1-E020 RO System
- Z1-E020 3-in-1 pre-post filter
- Z1-E020 RO membrane
- Power Transformer
- Inlet 3-way isolation valve
- Drain saddle & connector
- Brushed stainless steel tap and connector
- Tubing: 1.5m x 3/8" white 3m x 1/4" white

FEATURES & BENEFITS

- Push-fit connections for simple installation
- Cartridge change monitors
- Twist-and-lock cartridge loading
- Auto-flush settings to maintain quality
- All fittings included



Dimensions (mm)							
Code	Α	В	С				
Z1-E020	376	130	397				
Port Size (")							
Feed	Perm	eate	Concentrate				
3/8		4	1/4				

DIMENSIONS

RO SYSTEMS - Z1

SPECTRUM

P	ERFORMANCE		RATE
	Code	LPH (m³/day)	Avg Rejection (%)
	Z1-E020	120 (2.88)	@ 93

ORDERING GUIDE



System						
Code	Range	System Size	Туре			
Z1	E E	020	/			
Replacement Cartridges & Membranes						
Z1	E E	020	C - Cartidge			
Z1	E E	020	M - Membrane			

i.e Z1-E020

ASSOCIATED PRODUCTS

The below products have often been associated with this product.





REPLACEMENT 3 IN 1 CARTRIDGE Z1-E020-C

REPLACEMENT MEMBRANE Z1-E020-M